



# Life Saving and Safety Catalogue

## CONTENT PAGE

DESCRIPTION	PAGE	DESCRIPTION	PAGE
<b>FIRE FIGHTING EQUIPMENT AND PROTECTION</b>		<b>LIFE-SAVING AND PROTECTION</b>	
- Fire Blankets – Tested to BS 476 Part 7: 1997 KILLFIRE Model: KF-B	03	- Lifebuoy – DNV.GL Type Approved HAIXING Model: HXQ-5555	12
- Fireman Suits – DNV.GL Type Approved HAIZHOU Model: HZ-FC	04	- Lifebuoy Bracket HAIXING Model: HXJ	12
- Fireman’s Protective Suits - CCS Approved HAIZHOU Model: HZXF	05	- Quick Release Box for Lifebuoy HAIZHOU Model: HZ-09L0012	12
- Fireman’s Glove - DNV.GL Type Approved HAIZHOU Model: HZ-FG	05	- Lifebuoy Light - DNV.GL Type Approved HAIZHOU Model: HZ-09L0014B	12
- Portable Foam Applicator – DNV.GL Type Approved HAIZHOU Model: PQ8-C	06	<b>SIGNALS &amp; COMMUNICATION</b>	
- Safety Life Line – DNV.GL Type Approved HAIZHOU Model: HZL-I	06	- Cylinder Signal HAIZHOU Model: HZ-09L0042	13
<b>LIFE-SAVING AND PROTECTION</b>		- Double Cone Signal HAIZHOU Model: HZ-09L0044	13
- Self Contained Breathing Apparatus (SCBA) DNV.GL Type Approved HAIZHOU Model: HZ-RHZK6/30	07	- Ball Signal HAIZHOU Model: HZ-09L0041	13
Add on Accessory Cylinder Test Gauge HAIZHOU Model: HZ-RHZK6/30	07	- Cone Signal HAIZHOU Model: HZ-09L0043	13
- Emergency Escape Breathing Devices (EEBD) DNV.GL Type Approved HAIZHOU Model: HZ-THHZ15	07	- Diamond Signal HAIZHOU Model: HZ-09L0045	13
- Immersion Suit - DNV.GL Type Approved HAIZHOU Model: HXF-1	08		
- Immersion Suit - DNV.GL Type Approved HAIZHOU Model: HXF-2	08		
- Spray Tight Type Chemical Protective Suit DNV.GL Type Approved HAIXING Model: HXF-10	09		
- Air Tight Type Chemical Protective Suit DNV.GL Type Approved HAIXING Model: HXF-11	09		
- Fog Bell HAIZHOU Model: HZ-FB Series	10		
- Safety Drawing Canister HAIZHOU Model: HZ-09L0040	10		
- Life Jacket - DNV_GL Type Approved HAIZHOU Model: HZ-AJ-II (ADULT)	10		
- Life Jacket Light - DNV_GL Type Approved HAIZHOU Model: HZ-LJL	10		
- Double Fold Stretcher KILLFIRE Model: STRCHR-MDK-A102	11		



## Fire Blanket

Brand: KILLFIRE

Model: KF-B

Tested by TUV\_SUD\_PSB, Standard BS 476 Part 7: 1997

KILLFIRE Fire Blanket is made of 0.38mm thick, 100% Fibre Glass material which is resistant to high temperature. The material has good drapability and is efficient and durable giving outstanding extinguishing power. It is fitted with flame proof handles and uses Kevlar thread to ensure the blanket retains its highest integrity, giving the user confidence in the fiercest of fires.

### Features & Benefits:

- Pack fits snugly to wall
- Simple to use
- Maintenance free
- Easy storage and packing
- Flat top, no dirt build-up

### Packing Specification

Model	Blanket Size (m)	Packing Nett Weight (kg)	Packing Size (cm) L X W X H
KF-B-1.2	1.20 x 1.80	1.26	16.0 x 34.5 x 3.5
KF-B-1.8	1.80 x 1.80	1.86	16.0 x 48.5 x 3.5




Front View

Back View



## Fireman Suit



### Brand: HAIZHOU

**Standard:** SOLAS 1974, MSC.36(63), MSC.97(73), MSC.98(73), EN 469 (2005) including A (2006) and AC (2006)

Approved for use as protective clothing (close proximity clothing) for fire fighting as required by FSS code Ch.3 Para 2.1.1. Performance level achieved is Xf2, X32, Y2, Z2. The two-piece garment composed by a jacket and trousers, both must be worn together and must be used in combination with MED approved boots, gloves and helmet to provide the required protection.

- Sizes : 170A~190A (M, L, XL, XXL)
- Reflective trim, radio and box pockets

### Product Description

HZ-FC	
Colour	Red, Navy Blue and Khaki
Construction	4 layers
Outer fabric	93% meta-aramid, 5% para-aramid, 2% anti-static
Moisture barrier	65% aramid needlefelt, 20% PTFE, 15% PU
Thermal barrier	100% meta-aramid
Lining fabric	50% meta-aramid, 50% FR Viscose



Size No.	Chest (Max. cm)	Waist (Max. cm)	Height (cm)
M: 170A	≤120(120-124)	≤78(74-78)	166-174
L: 175A	≤128(124-128)	≤82(78-82)	171-179
XL: 180A	≤132(128-132)	≤86(78-82)	176-184
2XL: 185A	≤136(132-136)	≤90(82-90)	181-189
3XL: 190A	≤140(136-140)	≤94(90-94)	186-194



## Fireman Protective Suit - Aluminized




**Brand: HAIZHOU**

**Model: HZXF**

### Feature and Benefits

- Heat radiation resistance: Under heat radiation of 10KM/m<sup>2</sup>, about 30 seconds, the inside surface temperature shall rise not more than 25°C
- Material: Flame retardant fabric coated with aluminum foil
- Waterproof: Static hydraulic pressure ≥ 4000Pa
- Size: L
- Including: Jacket, trousers, gloves, boots and hood.

## Fireman Glove



**Brand: HAIZHOU**

**Model: HZ-FG**

**Standard: SOLAS 1974, MSC.36(63), MSC.97(73)**

### Feature and Benefits

- Waterproof and fire resistant
- Black split cowhide shell
- Kevlar fabric liner with moisture barrier
- Two-ply Kevlar wristlet with leather pull-tab cuff
- Size 10, XL (glove length 305mm)
- Colour: Black/yellow



### Portable Foam Applicator



Brand: HAIZHOU  
Model: PQ8-C

#### Feature and Benefits

- Standard: SOLAS 1974 and MSC.217(82)
- Total length: 1100 mm
- Working Pressure: 2.5-5 Bar
- Throwing Distance: over 20 m
- Flow rate: over 200 l/min
- Foam agent: 3% AFFF

---

### Safety Life Line



Brand: HAIZHOU  
Model: HZL-I

#### Feature and Benefits

- Standard: IMO Res. MSC.61(67)-(FTP Code) Annex 1 Part 1  
IMO Res. MSC.98(73)-(FSS Code) 3
- Material: Outer cover: fireproof PVC  
Inner core: Stainless Steel  
Hook: Stainless Steel
- Length: 30m
- Outer Diameter: 5mm, Core Diameter: 4mm
- Tensile Strength: over 3.5KN



### Self Contained Breathing Apparatus (SCBA)




**ADD ON ACCESSORY**

Cylinder Test Gauge  
Brand: HAIZHOU  
Model: HZ-PTG

**Design Details**

- Connection thread to air compressor, G5/8
- Pressure gauge for 0-400 bar




Brand: HAIZHOU  
Model: HZ-RHZK6/30

#### Technical Specification

Type	HZ-RHZK6/30	HZ-RHZK6.8/30A
Cylinder Material	Steel	Composite Carbon Fibre
Cylinder Volume	6L	6.8L
Compressed Air Capacity	1800L	2040L
Working Duration	Over 45 Min	Over 60 Min
Charging Pressure	300 bar	
Working Pressure	Over 45 Min	
Alarm Pressure	50~60 bar	
Weight	≤14kg	≤8.8kg
Cylinder Valve Charging Inlet	G5/8"	
Standard	EN136(1998) & EN137(2006) & MSC.339(91)	
Approvals	MED/DNV.GL/CCS	

### Emergency Escape Breathing Devices



Brand: HAIZHOU  
Model: HZ-THHZ15

#### Technical Specification




HZ-THHZ15	
Cylinder material	Steel
Cylinder volume	3L
Compressed air capacity	Over 540L
Working duration	Over 15 Min
Charging pressure	210 bar
Working pressure	3~210 bar
Flowrate	36L/Min
Weight	6kg
Cylinder valve charging inlet	G5/8"
Standard	EN1146:2005
Approval	MED/DNV.GL/CCS



### Immersion Suit



**DNV·GL**



**Brand: HAIZHOU**  
**Model: HXF-1**

#### Feature and Benefits


- Standard: SOLAS 1974/96 and amendment
- Neoprene product fabric
- Product floating: ≥ 150N
- At 0°C- +2°C history 6 hours in calm water, hypothermia does not exceed 2°C, with a life jacket lights, whistles, partners rope and pulling loop
- **To be worn together with life jackets**

Size	M	L	XL
<b>Fit for Height</b>	150~170cm	170~190cm	190~210cm

### Immersion Suit



**DNV·GL**



**Brand: HAIZHOU**  
**Model: HXF-2**

#### Feature and Benefits

- Standard: SOLAS 1974/96 and amendment
- Neoprene product fabric
- Product floating: ≥ 150N
- At 0°C- +2°C history 6 hours in calm water, hypothermia does not exceed 2°C, with a life jacket lights, whistles, partners rope and pulling loop

Size	M	L	XL
<b>Fit for Height</b>	150~170cm	170~190cm	190~210cm

## Spray Tight Type Chemical Protective Suit



Brand: HAIXING  
Model: HXF-10



### Feature and Benefits

- Standard: SOLAS 1974, as amended, in accordance with EN14605:2005
- Application: Used to protect fire fighting personnel from harmful chemicals and corrosive substances in a fire or accident. Complete set including chemical resistant suit, boots and gloves.
- Size: Free Size suitable for height up to 190cm

---

## Air Tight Type Chemical Protective Suit



Brand: HAIXING  
Model: HXF-11



### Feature and Benefits

- Standard: SOLAS 1974, as amended, in accordance with EN943-1:2002
- Used for on-site operation on dangerous chemicals or corrosive substances
- Size: Free Size suitable for height up to 190cm

**Fog Bell**



**Brand: HAIZHOU**  
**Model: HZ-09L0038 A/B**  
**Feature and Benefits**

- Material: Brass
- Audio Grade: ≥ 110 dB
- Origin: China

Model	Size Diameter
HZ-09L0038-A	Ø 200mm
HZ-09L0038-B	Ø 300mm

**Safety Drawing Canister**



**Brand: HAIZHOU**  
**Model: HZ-09L0040**


**Feature and Benefits**

- Material: PVC material
- Usage: Applied for storing of marine navigation chart, with mounting feet.

**Life Jacket**



**Brand: HAIZHOU**  
**Model: HZ-AJ-II (ADULT)**




**Feature and Benefits**

- Standard: SOLAS 1974/96 and amendment
- Fabric material: Polyester
- Product floating material: EPE
- Product floating: ≥ 150N
- Fit for height: ≥ 155cm
- Fit for weight: ≥ 43kg
- Certification: CE or CCS

**Life Jacket Light**



**Brand: HAIZHOU**  
**Model: HZ-LJL**



**Feature and Benefits**

- Standard: SOLAS 1974/96 and amendment
- LED light source
- Lithium battery power supply
- Touch water switch
- Light intensity: ≥ 0.75 CD
- Duration: ≥ 8 hours
- Certification: CE or CCS

## Double Fold Stretcher



**Brand: KILLFIRE**

**Model: STRCHR-MDK-A102**


### **Feature and Benefits**

- Outrigger is made of high strength aluminum alloy
- Canvas is waterproof, fireproof and easy to clean
- Foldable and comes with a bag
- Light weight and portable
- Product size (L x W x H): 208 x 55 x 13 cm
- Folding size (L x W x H): 104 x 17 x 9 cm
- Net weight: 4.7kg
- Gross weight: 11kg
- Load bearing: less than 159kg

### Lifebuoy



Brand: HAIXING  
Model: HXQ-5555



#### Feature and Benefits

- Standard: SOLAS 1974/96 and amendment
- Shell material: Low pressure high-density polyethylene
- Form material: Closed-cell polyurethane
- Product floating:  $\geq 14.5$  kg
- Certification: CE or CCS

Model	Internal Diameter (mm)	External Diameter (mm)	Height (mm)	Weight (kg)
HXQ-5555	$\varnothing 445 \pm 10$	$\varnothing 713 \pm 10$	90~105	2.5
HXQ-5555-4	$\varnothing 468 \pm 10$	$\varnothing 750 \pm 10$	105~120	4.3

### Lifebuoy Bracket



Brand: HAIXING  
Model: HXJ-Series

#### Feature and Benefits

- Spray powder surface treatment
- Support for HXQ-5555

Model	HXJ-1A	HXJ-1B	HXJ-1C	HXJ-1E
Material	Iron	SUS304	SUS316	Aluminum

### Quick Release Box for Lifebuoy



Brand: HAIZHOU  
Model: HZ-09L0012


#### Feature and Benefits

- Product material: FRP
- Fitting material: Stainless Steel
- A set of two, left and right side

### Lifebuoy Light



Brand: HAIZHOU  
Model: HZ-09L0014B



#### Feature and Benefits

- Standard: SOLAS 1974/96 and amendment
- LED light source
- Lithium battery power supply
- Touch water switch
- Light intensity: 2 CD
- Duration:  $\geq 2$  hours
- Certification: CE or CCS



### Ball Signal



**Brand: HAIZHOU**  
**Model: HZ-09L0041**  
**Feature and Benefits**

- Standard: According with 1972 the International Regulations for Preventing Collision at Sea 2003 Version.
- Product feature: Knitted with black rope
- Specification: Ø 600mm

---

### Cylinder Model




**Brand: HAIZHOU**  
**Model: HZ-09L0042**  
**Feature and Benefits**

- Standard: According with 1972 the International Regulations for Preventing Collision at Sea 2003 Version.
- Product feature: Knitted with black rope
- Specification: Ø 600mm x 1200mm

---

### Cone Signal




**Brand: HAIZHOU**  
**Model: HZ-09L0043**  
**Feature and Benefits**

- Standard: According with 1972 the International Regulations for Preventing Collision at Sea 2003 Version.
- Product feature: Knitted with black rope
- Specification: Ø 600mm

---

### Double Cone Signal




**Brand: HAIZHOU**  
**Model: HZ-09L0044**  
**Feature and Benefits**

- Standard: According with 1972 the International Regulations for Preventing Collision at Sea 2003 Version.
- Product feature: Knitted with black rope
- Specification: Ø 600mm x 1200mm

---

### Diamond Signal



**Brand: HAIZHOU**  
**Model: HZ-09L0045**  
**Feature and Benefits**

- Standard: According with 1972 the International Regulations for Preventing Collision at Sea 2003 Version.
- Product feature: Knitted with black rope
- Specification: Ø 600mm x 1200mm



Asiatic Fire System Pte Ltd  
No. 65 Joo Koon Circle,  
Singapore 629078  
Email: [asiatic@asiatic.com.sg](mailto:asiatic@asiatic.com.sg)



A subsidiary of the Asiatic Group (Holdings) Ltd  
**All rights reserved @2020**  
Specifications subject to change without prior notice  
KILLFIRE is a registered trademark